PRESSMAX

WASHMAX 60.10 MI

Blanket and Roller wash for use with conventional inks

Key Characteristics

Very strong cleaning power

Fogra approved

Water miscible

Corrosion inhibited

Flashpoint: 64°C

Suited for both manual and automatic use

Suited for coldset, heatset and sheetfed

Features and Benefits

Free of chlorinated hydrocarbons

Safer and lower environmental impact

Strong ink dissolving power

Fast acting, less standstills

Economical in use

Reduced downtime

Emulsifies with water

Stable emulsion

Reduced maintenance

Removes both ink and paper dust

Not aggressive to offset plate coating

Can be used for all common plate types

Instructions for use

Automatic systems: Follow the programme instructions.

Blankets: Apply with a moist cleaning rag and remove at one go ink and paper dust from the blanket. Then rub with a moist cloth until the blanket is dry.

Ink rollers: Spray undiluted or mixed with water on the rollers, set the doctor blade.

Transport & Storage

Protect the product from extreme climatic conditions. Do not store at temperatures above 35 °C or below -10 °C.

Take the necessary precautions to avoid that accidental leakage pollutes the environment.

For details about health and safety, please consult the MSDS.

Recommended auxiliaries

Water leveller: special additive added to the water tank of the washing unit

TEL +31 13 579 19 11
Graphic-arts-orderdesk_eu@fujifilm.com
www.fujifilm.eu/pressmax

FUJIFILM

1209PM-e_08